



Ministerie van Verkeer en Waterstaat

Flood Risk and Safety in the Netherlands (FLORIS) → *the method*

Tsukuba, October 1st 2009

Durk Riedstra
Rijkswaterstaat,
Centre for Water Management




Presentation


- Introduction
 - Current protection standards
 - 2nd Delta Committee → new risk based safety standards?
- The FLORIS project
 - Method
 - Results for two dike ring areas (river & sea)
 - Impact of risk reduction measures
- Time schedule new risk based approach




Flooding in the past



1st Delta Committee ('60s)




- These safety standard are NOT flood probabilities for a complete dike ring area



2nd Delta Committee (2008)

Current approach



'60s
exceedance frequency
overflow & wave overtopping
dike ring section
cost-benefit analysis



2nd Delta Committee (2008)

The new protection standards based should be based on:

- Basic level of protection for every citizen
→ Individual risk
- Risk aversion against many casualties
→ Societal risk
- Cost-benefit analyses


Instrument for water safety policy: FLORIS

→ www.deltacommissie.com




Failure mechanisms FLORIS

dikes







hydraulic structures




dunes

Method



Method




Risk reduction

Preparation / response
(emergency response)

Pro-action
(spatial planning)

Prevention






Method - Failure frequency

- FAILURE: Limited state condition = $\text{STRENGTH} - \text{LOAD} < 0$
 - Formulas for each failure mechanisms
 - Stochastic distribution (inherent en knowlegde uncertainties)
 - Failure frequency per mechanism per dike ring (section)

failure probably per dike ring area				
failure mechanism				all
dike section	overflow	instability inner slope	pipng	mechanism
1	4,2E-04	1,0E-06	n.a.	4,2E-04
2	3,7E-06	n.a.	2,8E-04	2,8E-04
3	2,3E-04	n.a.	1,9E-04	4,2E-04
...	...	...	...	...
total dike ring				3,3E-03

Method – Consequences (loss of life)

- Flood simulation
- Evacuation
 - warning, re
 - traffic mod
- Mortality funct



4 uur






Fig. 6. Mortality function and observations for the zone with rapidly rising waters.⁽³⁾




→ Deterministic n

Method – Consequences (economical damage)



Figuur 6.1: Verdeling verwachtingswaarde totale schade

- Flood simulation
 - maximum water level
- 'Economic value'
 - Type of industry
 - Density of houses
 - Loss of life (!)
 - € 6 million / casualty
- Indirect costs



Societal risk




Fig. 13. FN curve indicating the effects of two types of measures.



Ministerie van Verkeer en Waterstaat


Flood Risk and Safety in the Netherlands (FLORIS) → *first results*

Tsukuba, October 1st 2009

Durk Riedstra
Rijkswaterstaat,
Centre for Water Management



Method




RESULTS - 'RIVER' dike ring


- Along the river Rhine & IJssel
- 6 different flood scenario's identified
 - No multiple breaches

dike ring section	probability [per year]	dominant failure mode
48 - 1	2,92E-04	overflow and wave overtopping - dikes
48 - 2	5,95E-05	
48 - 3	2,55E-04	
48 - 4	6,57E-05	
48 - 5	3,16E-04	
48 - 6	7,72E-04	overflow and wave overtopping - dikes
total	1,76E-03	


- Flood probability dike ring area
 - Exceedance frequency 1




Flood simulations




Breach section 1 (south):
60-1000 casualties; damage: € 6 billion



Breach section 6 (north):
20-370 casualties;
damage: € 3,5 billion




Societal Risk



- Probability of >10 casualties: 2×10^{-3} /year
- Probability of >100 casualties: 1×10^{-3} /year
- Probability of >1000 casualties: $1,5 \times 10^{-5}$ /year


Economical damage



Figuur 6.1: Verdeling verwachtingswaarde totale schade



Risk reduction 1: Impact of higher dikes?

- A breach in section 1 results in:
 - almost complete dike ring area is flooded
 - many casualties & economical damage
 - overflow & wave overtopping dominant failure mechanism
- What is the effect of higher dikes at section 1?
(8% of the total dike ring length)





Individual risk: 20-25% risk reduction

- Current situation






with higher dikes in section 1

Societal risk




RESULTS - 'SEA' dike ring

- Partly along the North Sea (dunes)
- Mainly protected by dams
- 13 different flood scenario's identified
 - multiple breaches are possible




Individual Risk



Plaatsgebonden risico

- $<10^{-5}$
- $10^{-5}-10^{-4}$
- $10^{-4}-10^{-3}$
- $>10^{-3}$





Risk reduction 2: Impact of measures against piping?

- Measure:
→ increase of the water level in the polder during high water

water level in the polder	level	probability of flooding	
		[per year]	[per year]
normal winter level	low	0,056	1/18
during high water (outside polder):	high	0,003	1/325

- Flood probability decreases with almost a factor 20!
- Flood probability = 1/325 per year
 - Exceedance frequency per dike section 1/4000 year



First conclusions FLORIS project


(after risk assessment of 3 dike ring areas)

- The FLORIS method is a very useful tool to
 - determine the risk determining dike sections and failure mechanisms
 - Discriminate between more and less dangerous locations within a dike ring area
- High failure probabilities are found
 - defence system less safe than expected?
 - model too conservative (uncertainties)?
- Piping is a risk determining failure mechanism



Heading for new risk standards in 2011

- What should be the flood probability per dike ring and what will be the costs if:
 - Individual risk level of 10^{-5} /year is guaranteed?
 - and 10^{-6} /year?
 - An certain acceptable societal risk standard is proposed?
- And what will be the economic optimal flood probability per dike ring?






Time schedule


- 2011: a new risk based approach should be presented
- 2010: insight into costs of new risk based protection standards is necessary
- FLORIS not finished yet in 2011
 - 2010: results of 6 more dike rings available
 - 2011: 20 more dike rings ...
 - 2012: risk assessment of all 53 dike ring areas finished
- new approach should be based on a 'quick scan'
 - With input of only 9 FLORIS dike rings results ...



To be continued ...



Thanks for your attention
more information: [durk.riedstra @ rws.nl](mailto:durk.riedstra@rws.nl)



Special thanks to

- Harry Stefess & other FLORIS employees
- Ministry of Transport, Public Works and Water Management
- Water Board Union
- The 12 provinces